


スモールプランジャ



●規格仕様

	カタログ No.	A	B	C	D	F	スプリング圧 (kgf)	
							Min/Max	
SPS-□H ブラックノーズ (重荷重用)	SPS-5H	M5 × 0.8	12.0	1.5	2.5	2.5	0.5/1.5	
	SPS-6H	M6 × 1.0	13.0	1.5	3.0	3.0	0.6/2.0	
	SPS-8H	M8 × 1.25	15.0	2.0	4.0	4.0	0.6/2.0	
	SPS-10H	M10 × 1.5	16.0	2.5	5.0	5.0	1.0/3.0	
	SPS-12H	M12 × 1.75	20.0	3.5	6.0	6.0	1.0/3.0	
	SPS-16H	M16 × 2.0	22.0	4.5	8.0	8.0	2.0/6.0	
SPS-□L シルバーノーズ (軽荷重用)	SPS-5L	M5 × 0.8	12.0	1.5	2.5	2.5	0.2/0.8	
	SPS-6L	M6 × 1.0	13.0	1.5	3.0	3.0	0.3/1.0	
	SPS-8L	M8 × 1.25	15.0	2.0	4.0	4.0	0.3/1.0	
	SPS-10L	M10 × 1.5	16.0	2.5	5.0	5.0	0.5/1.5	
	SPS-12L	M12 × 1.75	20.0	3.5	6.0	6.0	0.5/1.5	
	SPS-16L	M16 × 2.0	22.0	4.5	8.0	8.0	1.0/3.0	

Order 注文例	形式
	例 SPS-10L

Delivery 納期	要相談
-----------------------	------------